CyberPower

CyberPower OR1500PFCRT2U alimentation d'énergie non interruptible Interactivité de ligne 1,5 kVA 900 W



Marque : CyberPower

Code produit: OR1500PFCRT2U

Nom du produit : OR1500PFCRT2U

CyberPower OR1500PFCRT2U. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 1,5 kVA, Puissance de sortie: 900 W. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 7 min, Temps de secours type à demi de charge: 21 min. Couleur du produit: Noir, Longueur de câble: 3 m, Type d'écran: LCD. Certification: UL1778, cUL 107.3, FCC DOC B, RoHS. Poids: 25,2 kg



Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	1,5 kVA
Puissance de sortie *	900 W
Fréquence d'entrée *	47/63 Hz
Estimation de montée subite d'énergie	1840 J
Temps de réponse	4 ms
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Alarmes sonores	✔

Connectivité	
Quantité de Ports USB 2.0	1
Nombre de ports série	2
Ports (RJ11) du modem	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	7 min
Temps de secours type à demi de charge	21 min

Batterie	
Temps de rechargement de la batterie	8 h
Batterie échangeable à chaud	✔
Cartouche de batterie de rechange	BP7-12/SH1228WFR

Design	
Longueur de câble	3 m
Couleur du produit *	Noir
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 35 °C
Humidité relative de fonctionnement (H-H)	0 - 90%

Certificat	
Certification	UL1778, cUL 107.3, FCC DOC B, RoHS

Poids et dimensions	
Poids	25,2 kg

Informations sur l'emballage	
Logiciels fournis	PowerPanel Business Edition

Autres caractéristiques	
Type de batterie	12V/7AH
Dimensions (LxPxH)	431,8 x 88,9 x 388,62 mm
Poids (impérial)	25,2 kg (55.5 kg)
Température d'opération	32 - 95 °F
Dimensions (L x L x H)	431,8 x 88,9 x 388,6 mm (17 x 3.5 x 15.3")

0649532609581

649532609581

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date