CyberPower PDU33108 unité de distribution d'énergie 42 sortie(s) CA 0U Noir

Marque : CyberPower

Code produit: PDU33108

Nom du produit : PDU33108

CyberPower PDU33108. Types de PDU: Avec contrôle en ligne, Capacité du rack: 0U, Type: Triphasé. Nombre de prises en sortie: 42 sortie(s) CA, Prise mâle: IEC 320. Voyants: Liaison, Statut, Longueur de câble: 3 m. Protocoles réseau pris en charge: IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL,..., Protocoles de gestion: UDP, Syslog, CLI, Windows AD, Mise à niveau du microprogrammable via: USB. Tension nominale à l'entrée: 200 - 240 V, Intensité (max.): 50 A, Fréquence d'entrée AC: 50 - 60 Hz



Design	
Types de PDU *	Avec contrôle en ligne
Type	Triphasé
Capacité du rack *	0U
Matériau du boîtier/corps	Métal
Couleur du produit	Noir
Écran	LCD

Connectivité	
Nombre de prises en sortie *	42 sortie(s) CA
Prise mâle	IEC 320
Nombre de port ethernet LAN (RJ-45)	2
Nombre de ports USB	1

Caractéristiques	
Voyants	Liaison, Statut
Longueur de câble	3 m

Caractéristiques de gestion	
Protocoles réseau pris en charge	IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL, LDAP(S), RADIUS
Protocoles de gestion	UDP, Syslog, CLI, Windows AD
Micrologiciel évolutif	✔
Mise à niveau du microprogrammable via	USB

Puissance	
Tension nominale à l'entrée *	200 - 240 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	50 A
Dispositifs de protection électrique	Surcharge

Certificat	
Certificats de conformité	RoHS

Conditions environnementales	
Température d'opération	-5 - 60 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3499 m
Température d'opération	23 - 140 °F

Poids et dimensions	
Largeur	56 mm
Profondeur	56 mm
Hauteur	1791 mm
Poids	7,98 kg

Informations sur l'emballage	
Poids du paquet	11,8 kg
Largeur du colis	215,9 mm
Profondeur du colis	160 mm
Hauteur du colis	2034,5 mm



0649532932849



649532932849

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date