CyberPower PDU41008 unité de distribution d'énergie 16 sortie(s) CA 2U Noir

Marque : CyberPower

Code produit: PDU41008

Nom du produit : PDU41008



CyberPower PDU41008. Types de PDU: Commutable, Capacité du rack: 2U, Type: Monophasé. Nombre de prises en sortie: 16 sortie(s) CA, Types de sortie AC: Coupleur C13, Coupleur C19, Prise mâle: NEMA L6-30P. Longueur de câble: 3,7 m. Surveillance: Courant, Énergie, Tension, Protocoles de gestion: IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPs, SSH, SSL,..., Mise à niveau du microprogrammable via: Réseau, USB. Tension nominale à l'entrée: 200-240 V, Intensité (max.): 30 A, Fréquence d'entrée AC: 50 - 60 Hz



Design	
Types de PDU *	Commutable
Type	Monophasé
Capacité du rack *	2U
Montage	horizontale/verticale
Matériau du boîtier/corps	Acier
Couleur du produit	Noir
Écran	LCD

Connectivité	
Nombre de prises en sortie *	16 sortie(s) CA
Prise mâle	NEMA L6-30P
Types de sortie AC *	Coupleur C13, Coupleur C19
Nombre de ports série	1
Nombre de port ethernet LAN (RJ-45)	1

Caractéristiques	
Voyants	✔
Longueur de câble	3,7 m

Caractéristiques de gestion	
Surveillance	Courant, Énergie, Tension
Protocoles de gestion	IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPs, SSH, SSL, TLS, LDAP(S), RADIUS, Syslog, CLI, Windows AD
Micrologiciel évolutif	✔
Mise à niveau du microprogrammable via	Réseau, USB

Puissance	
Tension nominale à l'entrée *	200-240 V

Puissance	
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	30 A
Tension nominale de sortie	200-240 V
Dispositifs de protection électrique	Surcharge

Certificat	
Certificats de conformité	RoHS
Certification	UL 60950, FCC A

Conditions environnementales	
Température d'opération	0 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3500 m
Altitude de non fonctionnement	0 - 15000 m

Poids et dimensions	
Largeur	433 mm
Profondeur	112 mm
Hauteur	88 mm
Poids	4,49 kg

Informations sur l'emballage	
Poids du paquet	6,48 kg
Largeur du colis	500 mm
Profondeur du colis	250 mm
Hauteur du colis	150 mm



0649532614141



649532614141

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date