CyberPower PDU41104 unité de distribution d'énergie 24 sortie(s) CA 0U

Marque : CyberPower

Code produit: PDU41104

Nom du produit : PDU41104

CyberPower PDU41104. Types de PDU: Commutable, Capacité du rack: 0U, Type: Monophasé. Nombre de prises en sortie: 24 sortie(s) CA, Types de sortie AC: NEMA 6–20P, Prise mâle: IEC 320. Voyants: Liaison, Statut, Longueur de câble: 3 m. Surveillance: Courant, Tension, Programme de gestion: IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL,..., Protocoles réseau pris en charge: UDP, Syslog, CLI, Windows AD. Tension nominale à l'entrée: 200 - 240 V, Intensité (max.): 20 A, Fréquence d'entrée AC: 50 - 60 Hz



Design	
Types de PDU *	Commutable
Type	Monophasé
Capacité du rack *	0U
Montage	verticale
Matériau du boîtier/corps	Acier
Écran	LCD

Connectivité	
Nombre de prises en sortie *	24 sortie(s) CA
Prise mâle	IEC 320
Types de sortie AC *	NEMA 6–20P
Nombre de port ethernet LAN (RJ-45)	2
Nombre de ports USB	1

Caractéristiques	
Voyants	Liaison, Statut
Longueur de câble	3 m

Caractéristiques de gestion	
Surveillance	Courant, Tension
Programme de gestion	IPv4, IPv6, HTTP, TLS, DNS, TCP/IP, DHCP, FTP, SNMPv1, NTP, Telnet, SMTP, SNMPv3, HTTPs, SSH, SSL, LDAP(S), RADIUS
Protocoles réseau pris en charge	UDP, Syslog, CLI, Windows AD
Micrologiciel évolutif	✔
Mise à niveau du microprogrammable via	USB

Puissance	
Tension nominale à l'entrée *	200 - 240 V
Fréquence d'entrée AC	50 - 60 Hz
Intensité (max.) *	20 A

Certificat	
Certificats de conformité	RoHS

Conditions environnementales	
Température d'opération	0 - 60 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Température d'opération	32 - 140 °F

Poids et dimensions	
Largeur	55,9 mm
Profondeur	48,3 mm
Hauteur	1663,7 mm
Poids	7,8 kg

Contenu de l'emballage	
Câbles inclus	LAN (RJ-45)
Manuel d'utilisation	✔
Kit de montage en rack	✔
Contenu de l'emballage	PDU, 2 Mounting Brackets, 6 (Flat Head M4x5) Bracket Mounting Screws, 6 (M5x12) Rack Mounting Screws/Washers, Cord Retention Tray, 36 Cable Ties, 6 (M3x6) Cord Retention Tray Mounting Screws, RJ45/DB9 Serial Port Connection Cable, 10ft Power Cord IEC-320 C19 to NEMA L6-20P, Registration and Software Download Cards



0649532618668



649532618668

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date