ASUS PN53-BB7000X1TDR-NL Taille pc 0.92l Noir

Marque : ASUS

Code produit: 90MR00S2-M002H0

Nom du produit : PN53-BB7000X1TDR-NL



ASUS PN53-BB7000X1TDR-NL. Type de châssis: Taille pc 0.92l, Type de produit: Mini PC type barebone. Types de mémoire pris en charge: DDR5-SDRAM, Nombre de logements pour mémoire: 2, Mémoire interne maximale: 32 Go. Types de lecteurs de stockage pris en charge: HDD & SSD, D'interface pour unité de stockage: PCI Express, Série ATA III. Nombre de port ethernet LAN (RJ-45): 1. Standards wifi: Wi-Fi 6E (802.11ax), Modèle du Bluetooth: 5.3. Type de refroidissement: Actif



Processeur	
Fabricant de processeur	AMD
Intégré dans le processeur *	✗
Mémoire	
Type de support (slot) *	SO-DIMM
Nombre de logements pour mémoire *	2
Mémoire interne maximale	32 Go
Prise en charge de la mémoire vitesse d'horloge	4800 MHz
Types de mémoire pris en charge	DDR5-SDRAM
Support de stockage	
Types de lecteurs de stockage pris en charge *	HDD & SSD
Tailles de disque de stockage pris en charge *	2.5,M.2
D'interface pour unité de stockage	PCI Express, Série ATA III
Nombre d'unités de stockage pris en charge	3
Graphique	
Carte graphique intégrée *	✗
représentation / réalisation	
Nombre de processeurs pris en charge	1
Puce audio	Realtek ALC897
Audio	
Haut-parleurs intégrés *	✗
Réseau	
Norme Wi-Fi	Wi-Fi 6E (802.11ax)
Standards wifi	Wi-Fi 6E (802.11ax)
Ethernet/LAN *	✔

Réseau	
Wifi *	✔
Contrôleur de réseau local (LAN)	Realtek RTL8125B-CG
Bluetooth	✔
Modèle du Bluetooth	5.3
Connectivité	
Quantité de ports de type A USB 3.2 Gen 1 (3.1 Gen 1) *	5
Quantité de ports USB4 Gen 2x2	2
Quantité de ports HDMI *	2
Version HDMI	2.1
Entrée jack microphone	✔
Sortie de casque	1
Nombre de port ethernet LAN (RJ-45) *	1
Entrée DC	✔
Design	
Type de châssis *	Taille pc 0.92l
Couleur du produit *	Noir
Type de refroidissement *	Actif
Bouton marche/arrêt intégré	✔
Port de câble antivol	✔
Type d'emplacement de verrouillage de câble	Kensington
Type de produit *	Mini PC type barebone
Puissance	
Type d'alimentation d'énergie *	Adaptateur CA externe
Poids et dimensions	
Largeur	120 mm
Profondeur	130 mm
Hauteur	58 mm
Poids	900 g

Réseau	
Technologie de câblage Ethernet cuivre	2500BASE-T

0197105291317

197105291317

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date