CyberPower PR2000RTXL2UTAA alimentation d'énergie non interruptible Interactivité de ligne 2 kVA 2000 W 8 sortie(s) CA

Marque : CyberPower

Code produit: PR2000RTXL2UTAA

Nom du produit : PR2000RTXL2UTAA



CyberPower PR2000RTXL2UTAA. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 2 kVA, Puissance de sortie: 2000 W. Types de sortie AC: NEMA L5-20R, Prise mâle: NEMA 5-20P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 9 Ah, Tension des piles: 12 V. Format: Rack/Tour, Couleur du produit: Noir, Capacité du rack: 2U. Largeur: 434 mm, Profondeur: 500 mm, Hauteur: 86 mm



Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	2 kVA
Puissance de sortie *	2000 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	100 V
Tension de voltage à l'entrée (max) *	125 V
Fréquence d'entrée *	47/63 Hz
Intensité (max.)	20 A
Estimation de montée subite d'énergie	2430 J
Temps de réponse	4 ms
Filtre de bruit EMI/RFI	✔
Alarmes sonores	✔
Modes d'alarme sonore	Alarme en mode batterie, Alarme de batterie faible, Alarme de surcharge

Connectivité	
Types de sortie AC	NEMA L5-20R
Prise mâle	NEMA 5-20P
Nombre de prises en sortie	8 sortie(s) CA
Nombre de port ethernet LAN (RJ-45)	2

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	9 Ah
Tension des piles	12 V
Temps de secours type au chargement complet	4,3 min

Batterie	
Temps de secours type à demi de charge	12,2 min
Temps de rechargement de la batterie	3 h

Design	
Format *	Rack/Tour
Capacité du rack	2U
Longueur de câble	3 m
Couleur du produit *	Noir
Voyants	Remplacement de batterie, Panne, Énergie

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3048 m
Altitude de non fonctionnement	0 - 15000 m

Poids et dimensions	
Largeur	434 mm
Profondeur	500 mm
Hauteur	86 mm
Poids	33,8 kg

Informations sur l'emballage	
Largeur du colis	561,3 mm
Profondeur du colis	619,8 mm
Hauteur du colis	274,3 mm
Poids du paquet	40,2 kg



0649532931453



649532931453

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date