CyberPower

CyberPower SL700U alimentation d'énergie non interruptible Veille 0,7 kVA 370 W 8 sortie(s) CA



Marque : CyberPower

Code produit: SL700U

Nom du produit : SL700U

CyberPower SL700U. Topologie UPS: Veille, capacité de la puissance de sortie: 0,7 kVA, Puissance de sortie: 370 W. Prise mâle: NEMA 5-15P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 5,5 Ah, Tension des piles: 12 V. Format: Compact, Couleur du produit: Noir, Longueur de câble: 1,5 m. Câbles inclus: Cable d'éntrée



Caractéristiques	
Topologie UPS *	Veille
capacité de la puissance de sortie *	0,7 kVA
Puissance de sortie *	370 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	96 V
Tension de voltage à l'entrée (max) *	140 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
fréquence de sortie	50/60 Hz
Régulation de la tension de sortie	5%
Régulateur de tension automatique (AVR)	✔
Intensité (max.)	15 A
Estimation de montée subite d'énergie	890 J
Temps de réponse	8 ms
Filtre de bruit EMI/RFI	✔
Protection contre les surtensions	✔
Alarmes sonores	✔
Modes d'alarme sonore	Alarme de batterie faible, Alarme de surcharge

Connectivité	
Prise mâle	NEMA 5-15P
Nombre de prises en sortie	8 sortie(s) CA
Port USB	✔

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	5,5 Ah

Batterie	
Tension des piles	12 V
Nombre de cellules de batterie	1
Temps de secours type au chargement complet	2 min
Temps de secours type à demi de charge	9 min
Temps de rechargement de la batterie	8 h

Design	
Format *	Compact
Longueur de câble	1,5 m
Couleur du produit *	Noir
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%

Contenu de l'emballage	
Câbles inclus	Cable d'éntrée

Safety regulation & standards	
Sécurité	UL1778, cUL, FCC DOC Class B, CEC

Poids et dimensions	
Largeur	324 mm
Profondeur	70 mm
Hauteur	137 mm
Poids	3,07 kg

Informations sur l'emballage	
Largeur du colis	152,4 mm
Profondeur du colis	361,9 mm

Informations sur l'emballage	
Hauteur du colis	171,4 mm
Poids du paquet	3,27 kg



0649532930791



649532930791

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date