APC SMC1000-2UC alimentation d'énergie non interruptible Interactivité de ligne 1 kVA 600 W

Marque : APC

Code produit: SMC1000-2UC

Nom du produit : SMC1000-2UC



APC SMC1000-2UC. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 1 kVA, Puissance de sortie: 600 W. Durée de vie totale de la batterie (max): 6 année(s), Temps de rechargement de la batterie: 3 h. Couleur du produit: Noir, Type d'écran: LCD. Compliance certificates: RoHS, Certification: CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778. Câbles inclus: Câble USB



Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	1 kVA
Puissance de sortie *	600 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	93 V
Tension de voltage à l'entrée (max) *	130 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	110 V
Tension de voltage à la sortie (max)	125 V
fréquence de sortie	50/60 Hz
Régulateur de tension automatique (AVR)	✔
Estimation de montée subite d'énergie	680 J
Temps de réponse	10 ms
Niveau sonore	41 dB
Alarmes sonores	✔
Modes d'alarme sonore	Alarme en mode batterie, Alarme de batterie faible

Connectivité	
Port USB	✔
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Durée de vie totale de la batterie (max)	6 année(s)
Temps de rechargement de la batterie	3 h

Batterie	
Batterie échangeable à chaud	✔
Démarrage à froid	✔

Design	
Couleur du produit *	Noir
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3048 m
Altitude de non fonctionnement	0 - 15240 m

Certificat	
Certificats de conformité	RoHS
Certification	CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778

Contenu de l'emballage	
Kit de montage en rack	✔
Câbles inclus	Câble USB

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	432 mm
Profondeur	406 mm
Hauteur	86 mm
Poids	20,5 kg

Informations sur l'emballage	
Largeur du colis	535 mm
Profondeur du colis	570 mm

Informations sur l'emballage	
Hauteur du colis	235 mm
Poids du paquet	20,7 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date