APC SMT3000RM2U alimentation d'énergie non interruptible 3 kVA 2700 W 8 sortie(s) CA





Marque : APC

Code produit: SMT3000RM2U

Nom du produit : SMT3000RM2U

Smart-UPS 3000VA, RM, 2U, LCD, 120V
APC SMT3000RM2U. capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 2700 W, Tension de voltage à l'entrée (min): 75 V. Types de sortie AC: NEMA 5–15R, NEMA 5–20R, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 3 h. Format: A mettre sur rack, Couleur du produit: Noir, Capacité du rack: 2U. Certification: CSA,FCC 15 A,UL 1778

Caractéristiques	
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	2700 W
Tension de voltage à l'entrée (min) *	75 V
Tension de voltage à l'entrée (max) *	154 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
Estimation de montée subite d'énergie	459 J
Efficacité	98%
Niveau sonore	55 dB
Alarmes sonores	✔

Connectivité	
Types de sortie AC	NEMA 5–15R, NEMA 5–20R
Nombre de prises en sortie	8 sortie(s) CA

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de rechargement de la batterie	3 h

Design	
Format *	A mettre sur rack
Capacité du rack	2U

Design	
Longueur de câble	2,44 m
Couleur du produit *	Noir

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certification	CSA,FCC 15 A,UL 1778

Poids et dimensions	
Largeur	480 mm
Profondeur	683 mm
Hauteur	86 mm
Poids	44,3 kg

Informations sur l'emballage	
Poids du paquet	51,7 kg

Autres caractéristiques	
Type de batterie	RBC43
Interface	USB
Tension nominale de sortie	120 V
Tension nominale à l'entrée	120 V
Dimensions du colis (LxPxH)	600 x 980 x 254 mm

0731304279549

731304279549

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date