APC Smart-UPS alimentation d'énergie non interruptible 2,88 kVA 2700 W 8 sortie(s) CA





Marque : APC

Code produit: SMT3000RMUS

Nom du produit : Smart-UPS

APC Smart-UPS. capacité de la puissance de sortie: 2,88 kVA, Puissance de sortie: 2700 W, Forme d'onde: Sinus. Types de sortie AC: NEMA 5–15R, NEMA 5–20R, Prise mâle: NEMA L5-30P, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 3,4 min, Temps de secours type à demi de charge: 7,2 min. Format: A mettre sur rack, Couleur du produit: Gris, Capacité du rack: 2U. Compliance certificates: RoHS

Caractéristiques	
capacité de la puissance de sortie *	2,88 kVA
Puissance de sortie *	2700 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	75 V
Tension de voltage à l'entrée (max) *	154 V
Fréquence d'entrée *	50/60 Hz
Estimation de montée subite d'énergie	459 J
Efficacité	98%
Tension de sortie THD	5%
Niveau sonore	55 dB
Alarmes sonores	✔
Modes d'alarme sonore	Remplacement de batterie

Connectivité	
Types de sortie AC	NEMA 5–15R, NEMA 5–20R
Prise mâle	NEMA L5-30P
Nombre de prises en sortie	8 sortie(s) CA
Quantité de Ports USB 2.0	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	3,4 min
Temps de secours type à demi de charge	7,2 min
Temps de rechargement de la batterie	3 h
Cartouche de batterie de rechange	RBC43

Design	
Format *	A mettre sur rack
Capacité du rack	2U
Longueur de câble	2,44 m
Couleur du produit *	Gris
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certificats de conformité	RoHS

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	480 mm
Profondeur	683 mm
Hauteur	86 mm
Poids	44,3 kg

Informations sur l'emballage	
Poids du paquet	51,7 kg

Autres caractéristiques	
Tension nominale de sortie	120 V
Tension nominale à l'entrée	120 V
Type de connexion de sortie	6 x NEMA 5-15R & 2 x NEMA 5-20R
Dimensions du colis (LxPxH)	600 x 980 x 254 mm



0731304305637



731304305637

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date