APC SMTL2200RM2UCNC alimentation d'énergie non interruptible Interactivité de ligne 2,2 kVA 1920 W 8 sortie(s) CA


Marque : APC

Code produit: SMTL2200RM2UCNC

Nom du produit : SMTL2200RM2UCNC



APC SMTL2200RM2UCNC. Topologie UPS: Interactivité de ligne, capacité de la puissance de sortie: 2,2 kVA, Puissance de sortie: 1920 W. Types de sortie AC: NEMA 5–15R, NEMA 5–20R, Nombre de prises en sortie: 8 sortie(s) CA, Type d'interface série: RJ-45. Technologie batterie: Lithium-Ion (Li-Ion), Temps de secours type au chargement complet: 6 min, Temps de secours type à demi de charge: 12 min. Format: A mettre sur rack, Couleur du produit: Noir, Argent, Capacité du rack: 2U. Certification: CSA C22.2 No 107.1, CULus, FCC part 15 class A, UL 1778, UL 1973



Caractéristiques	
Topologie UPS *	Interactivité de ligne
capacité de la puissance de sortie *	2,2 kVA
Puissance de sortie *	1920 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	82 V
Tension de voltage à l'entrée (max) *	144 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	120 V
fréquence de sortie	50/60 Hz
Régulation de la tension de sortie	5%
Estimation de montée subite d'énergie	530 J
Efficacité	96%
Niveau sonore	55 dB

Connectivité	
Types de sortie AC	NEMA 5–15R, NEMA 5–20R
Nombre de prises en sortie	8 sortie(s) CA
Port USB	✔
Interface série	✔
Type d'interface série	RJ-45
Nombre de port ethernet LAN (RJ-45)	1
SmartSlot	✔

Batterie	
Technologie batterie	Lithium-Ion (Li-Ion)
Temps de secours type au chargement complet	6 min

Batterie	
Temps de secours type à demi de charge	12 min

Design	
Format *	A mettre sur rack
Capacité du rack	2U
Couleur du produit *	Noir, Argent
Type d'écran	LCD
Voyants	✔
Code (IP) Internationale Protection	IP20

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 7620 m

Certificat	
Certification	CSA C22.2 No 107.1, CULus, FCC part 15 class A, UL 1778, UL 1973

Poids et dimensions	
Largeur	432,1 mm
Profondeur	683 mm
Hauteur	86,1 mm
Poids	31,9 kg

Informations sur l'emballage	
Largeur du colis	600 mm
Profondeur du colis	980,4 mm
Hauteur du colis	254 mm
Poids du paquet	39,2 kg



0731304429111



731304429111

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date