APC SMX2200RMLV2U alimentation d'énergie non interruptible 2,2 kVA 1980 W





Marque : APC

Code produit: SMX2200RMLV2U

Nom du produit : SMX2200RMLV2U

APC SMX2200RMLV2U. capacité de la puissance de sortie: 2,2 kVA, Puissance de sortie: 1980 W, Tension de voltage à l'entrée (min): 70 V. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 7 min, Temps de secours type à demi de charge: 26 min. Format: Rack/Tour, Couleur du produit: Noir, Capacité du rack: 2U. Compliance certificates: RoHS, Certification: NOM, TUV, UL, FCC. Largeur: 431 mm, Profondeur: 667 mm, Hauteur: 85 mm

Caractéristiques	
capacité de la puissance de sortie *	2,2 kVA
Puissance de sortie *	1980 W
Tension de voltage à l'entrée (min) *	70 V
Tension de voltage à l'entrée (max) *	153 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	100 V
Tension de voltage à la sortie (max)	127 V
Estimation de montée subite d'énergie	540 J
Temps de réponse	2 ms
Efficacité	97,6%
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Niveau sonore	55 dB
Protection contre les surtensions	✔

Connectivité	
Quantité de Ports USB 2.0	1
Nombre de ports série	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de secours type au chargement complet	7 min

Batterie	
Temps de secours type à demi de charge	26 min
Temps de rechargement de la batterie	3 h
Batterie échangeable à chaud	✔

Design	
Format *	Rack/Tour
Capacité du rack	2U
Longueur de câble	2,44 m
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	Remplacement de batterie

Certificat	
Certificats de conformité	RoHS
Certification	NOM, TUV, UL, FCC

Poids et dimensions	
Largeur	431 mm
Profondeur	667 mm
Hauteur	85 mm
Poids	38,5 kg

Informations sur l'emballage	
Poids du paquet	45,4 kg

Données logistiques	
Code du système harmonisé	85078000

Autres caractéristiques	
Interface	RJ45/USB
Type de connexion d'entrée	NEMA L5-30P
Tension nominale de sortie	120 V
Tension nominale à l'entrée	120 V
Dimensions du colis (LxPxH)	596 x 869 x 243 mm

0731304268567

731304268567

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date