APC SRT5KXLT alimentation d'énergie non interruptible Double-conversion (en ligne) 5 kVA 4250 W 4 sortie(s) CA



Marque : APC

Code produit: SRT5KXLT

Nom du produit : SRT5KXLT

APC SRT5KXLT. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 5 kVA, Puissance de sortie: 4250 W. Types de sortie AC: NEMA L6-20R, NEMA L6-30R, Prise mâle: NEMA L6-30P, Nombre de prises en sortie: 4 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 1,50 h. Format: Compact, Couleur du produit: Noir, Longueur de câble: 3,05 m. Compliance certificates: RoHS, Certification: CSA, FCC, NOM, UL



Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	5 kVA
Puissance de sortie *	4250 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	160 V
Tension de voltage à l'entrée (max) *	275 V
Fréquence d'entrée *	40/70 Hz
Tension de voltage à la sortie (max)	240 V
fréquence de sortie	50/60 Hz
Estimation de montée subite d'énergie	480 J
Facteur de crête	3:1
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Tension de sortie THD	2%
Niveau sonore	55 dB
Alarmes sonores	✔

Connectivité	
Types de sortie AC	NEMA L6-20R, NEMA L6-30R
Prise mâle	NEMA L6-30P
Nombre de prises en sortie	4 sortie(s) CA
Quantité de Ports USB 2.0	1
Nombre de ports série	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)

Batterie	
Temps de rechargement de la batterie	1,50 h

Design	
Format *	Compact
Longueur de câble	3,05 m
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certificats de conformité	RoHS
Certification	CSA, FCC, NOM, UL

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	130 mm
Profondeur	719 mm
Hauteur	432 mm
Poids	55,8 kg

Informations sur l'emballage	
Largeur du colis	610 mm
Profondeur du colis	960 mm
Hauteur du colis	330 mm

Informations sur l'emballage	
Poids du paquet	64,4 kg
Données logistiques	
Quantité par palette	6 pièce(s)

0731304301622

731304301622

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date