APC SRT6KRMXLT alimentation d'énergie non interruptible Double-conversion (en ligne) 6 kVA 6000 W 6 sortie(s) CA

Marque : APC

Code produit: SRT6KRMXLT

Nom du produit : SRT6KRMXLT



APC SRT6KRMXLT. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 6 kVA, Puissance de sortie: 6000 W. Types de sortie AC: NEMA L6-20R, NEMA L6-30R, Nombre de prises en sortie: 6 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 1,50 h. Format: A mettre sur rack, Couleur du produit: Noir, Capacité du rack: 4U. Compliance certificates: RoHS, Certification: CSA, FCC, NOM, UL



Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	6 kVA
Puissance de sortie *	6000 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	100 V
Tension de voltage à l'entrée (max) *	275 V
Fréquence d'entrée *	40/70 Hz
Tension de voltage à la sortie (max)	240 V
Estimation de montée subite d'énergie	480 J
Facteur de crête	3:1
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Tension de sortie THD	2%

Connectivité	
Types de sortie AC	NEMA L6-20R, NEMA L6-30R
Nombre de prises en sortie	6 sortie(s) CA
Quantité de Ports USB 2.0	1
Nombre de ports série	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Temps de rechargement de la batterie	1,50 h

Design	
Format *	A mettre sur rack
Capacité du rack	4U
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔
Code (IP) Internationale Protection	IP20

Conditions environnementales	
Température d'opération	0 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certificats de conformité	RoHS
Certification	CSA, FCC, NOM, UL

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	432 mm
Profondeur	719 mm
Hauteur	174 mm
Poids	61,2 kg

Informations sur l'emballage	
Largeur du colis	610 mm
Profondeur du colis	960 mm
Hauteur du colis	370 mm
Poids du paquet	68 kg

Données logistiques	
Quantité par palette	6 pièce(s)



0731304308522



731304308522

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date