APC SRTL3KRM1UC alimentation d'énergie non interruptible Double-conversion (en ligne) 3 kVA 2880 W 6 sortie(s) CA

Marque : APC

Code produit: SRTL3KRM1UC

Nom du produit : SRTL3KRM1UC



APC SRTL3KRM1UC. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 2880 W. Types de sortie AC: NEMA L5-30R, Prise mâle: NEMA L5-30P, Nombre de prises en sortie: 6 sortie(s) CA. Technologie batterie: Lithium-Ion (Li-Ion), Temps de rechargement de la batterie: 1,5 h. Format: A mettre sur rack, Couleur du produit: Gris, Capacité du rack: 1U. Compliance certificates: RoHS



Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	2880 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	120 V
Tension de voltage à l'entrée (max) *	125 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	125 V
fréquence de sortie	50/60 Hz
Efficacité	93%
Niveau sonore	55 dB
Alarmes sonores	✔

Connectivité	
Types de sortie AC	NEMA L5-30R
Prise mâle	NEMA L5-30P
Nombre de prises en sortie	6 sortie(s) CA
Port USB	✔
Type de port USB	USB Type-A

Batterie	
Technologie batterie	Lithium-Ion (Li-Ion)
Temps de rechargement de la batterie	1,5 h

Design	
Format *	A mettre sur rack
Capacité du rack	1U
Longueur de câble	2,44 m
Type de refroidissement	Passif
Couleur du produit *	Gris
Type de commande	Boutons
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3048 m

Certificat	
Certificats de conformité	RoHS

Sustainability	
Ne contient pas	Mercure

Poids et dimensions	
Largeur	432 mm
Profondeur	560 mm
Hauteur	43 mm
Poids	15,9 kg

Informations sur l'emballage	
Largeur du colis	564 mm
Profondeur du colis	764 mm
Hauteur du colis	278,2 mm
Poids du paquet	24,2 kg



0731304435532



731304435532

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date