APC SRTL3KRM1UWC alimentation d'énergie non interruptible Double-conversion (en ligne) 3 kVA 3000 W 5 sortie(s) CA



Marque : APC

Code produit: SRTL3KRM1UWC

Nom du produit : SRTL3KRM1UWC



APC SRTL3KRM1UWC. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 3000 W. Types de sortie AC: Coupleur C13, Coupleur C19, Prise mâle: BS1363A, Nombre de prises en sortie: 5 sortie(s) CA. Technologie batterie: Lithium-Ion (Li-Ion), Tension des piles: 50 V, Temps de rechargement de la batterie: 1,5 h. Format: A mettre sur rack, Couleur du produit: Argent, Capacité du rack: 1U. Compliance certificates: CE, Certification: EN/IEC 62040-1

Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	3000 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	208 V
Tension de voltage à l'entrée (max) *	240 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	208 V
Tension de voltage à la sortie (max)	240 V
fréquence de sortie	50/60 Hz
Facteur de crête	3:1
Niveau sonore	55 dB
Alarmes sonores	✔

Connectivité	
Types de sortie AC	Coupleur C13, Coupleur C19
Prise mâle	BS1363A
Nombre de prises en sortie	5 sortie(s) CA
Port USB	✔
Quantité de Ports USB 2.0	1
Type de port USB	USB Type-B
Interface série	✔
Nombre de ports série	1
Nombre de port ethernet LAN (RJ-45)	1
Connecteur de coupure d'alimentation d'urgence	✔

Batterie	
Technologie batterie	Lithium-Ion (Li-Ion)
Tension des piles	50 V

Batterie	
Temps de rechargement de la batterie	1,5 h
Cartouche de batterie de rechange	APCRBC173-LI

Design	
Format *	A mettre sur rack
Capacité du rack	1U
Longueur de câble	2,4 m
Couleur du produit *	Argent
Type d'écran	LCD
Code (IP) Internationale Protection	IP20

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15240 m

Certificat	
Certificats de conformité	CE
Certification	EN/IEC 62040-1

Poids et dimensions	
Largeur	432 mm
Profondeur	560 mm
Hauteur	43 mm
Poids	15,9 kg

Informations sur l'emballage	
Largeur du colis	564 mm
Profondeur du colis	764 mm
Hauteur du colis	278 mm
Poids du paquet	24,2 kg

0731304573524

731304573524

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date