APC SRYL10K15RMXLT alimentation d'énergie non interruptible Double-conversion (en ligne) 3 kVA 2700 W 8 sortie(s) CA





Marque : APC

Code produit: SRYL10K15RMXLT

Nom du produit : Onduleur APC Easy UPS SRV 6 000 VA 230 V

APC SRYL10K15RMXLT. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 2700 W. Types de sortie AC: IEC 60320, Prise mâle: BS1363A, Nombre de prises en sortie: 8 sortie(s) CA. Technologie batterie: Plomb-Acide, Tension des piles: 96 V, Durée de vie totale de la batterie (max): 5 année(s). Format: Tower, Couleur du produit: Noir, Longueur de câble: 2,4 m. Compliance certificates: CE, cULus

Caractéristiques	
Topologie UPS *	Double-conversion (en ligne)
capacité de la puissance de sortie *	3 kVA
Puissance de sortie *	2700 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	100 V
Tension de voltage à l'entrée (max) *	275 V
Fréquence d'entrée *	40 - 70 Hz
tension de voltage à la sortie (min)	220 V
fréquence de sortie	50/60 Hz
Régulation de la fréquence de sortie	3 Hz
Dissipation thermique	703 BTU/h
Nombre de phases d'entrée	1
Nombre de phases de sortie	1
Facteur de crête	3:1
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Tension de sortie THD	2%
Niveau sonore	55 dB

Connectivité	
Types de sortie AC	IEC 60320
Prise mâle	BS1363A
Nombre de prises en sortie	8 sortie(s) CA
Port USB	✔
Interface série	✔
Fente pour carte réseau	✔
SmartSlot	✔

Batterie	
Technologie batterie	Plomb-Acide

Batterie	
Tension des piles	96 V
Durée de vie totale de la batterie (max)	5 année(s)
Temps de rechargement de la batterie	3 h

Design	
Format *	Tower
Longueur de câble	2,4 m
Couleur du produit *	Noir

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 10000 m
Altitude de non fonctionnement	0 - 15240 m

Certificat	
Certificats de conformité	CE, cULus

Sustainability	
Certificats de durabilité	ENERGY STAR

Poids et dimensions	
Largeur	85 mm
Profondeur	635 mm
Hauteur	432 mm
Poids	31,3 kg

Informations sur l'emballage	
Largeur du colis	871 mm
Profondeur du colis	599 mm
Hauteur du colis	246 mm
Poids du paquet	36,7 kg



0731304420125



731304420125

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date