StarTech.com ST4300USB3V2-NA hub & concentrateur USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Noir



Marque : StarTech.com

Code produit: ST4300USB3V2-NA

Nom du produit : ST4300USB3V2-NA

StarTech.com ST4300USB3V2-NA. Interface de l'hôte: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Interfaces Hub: USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Taux de transfert de données: 5000 Mbit/s, Couleur du produit: Noir, Matériau du boîtier/corps: Plastique. Consommation électrique typique: 24 W, Tension d'entrée: 100 - 240 V, Courant d'entrée: 0.7 A. Largeur: 52 mm, Profondeur: 101 mm, Hauteur: 16,5 mm. Quantité: 1 pièce(s), Largeur du colis: 200 mm, Profondeur du colis: 147 mm





Connectivité	
Interface de l'hôte *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
Interfaces Hub *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
Quantité de ports de type A USB 3.2 Gen 1 (3.1 Gen 1)	4
Quantité de ports *	4
Entrée DC	✔

Caractéristiques	
Taux de transfert de données *	5000 Mbit/s
Couleur du produit	Noir
Matériau du boîtier/corps	Plastique
Voyants	✔
Matériau de la prise du câble	Élastomère thermoplastique (TPE)
Longueur de câble	1 m

Puissance	
Consommation électrique typique	24 W
Tension d'entrée	100 - 240 V
Courant d'entrée	0.7 A
Tension de sortie	12 V
Courant de sortie	2 A

Poids et dimensions	
Largeur	52 mm
Profondeur	101 mm
Hauteur	16,5 mm
Poids	55,9 g

Informations sur l'emballage	
Quantité	1 pièce(s)
Largeur du colis	200 mm
Profondeur du colis	147 mm
Hauteur du colis	49 mm
Poids du paquet	340,5 g

Contenu de l'emballage	
Adaptateurs d'interface inclus	USB Type-C Femelle- USB Type-A Mâle
Adaptateur secteur fourni	✔
Types de fiches d'alimentation fournies	ANZ, NA, JP
Câbles inclus	USB Type-C vers USB Type-C

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 60 °C
Humidité relative de fonctionnement (H-H)	0 - 90%

représentation / réalisation	
Temps moyen entre pannes	117452 h

Données logistiques	
Largeur du carton principal	430 mm
Longueur du carton principal	275 mm
Hauteur du carton principal	325 mm
Quantité par carton principal	20 pièce(s)

Autres caractéristiques	
Jeu de composants	VIA - VL817S



0065030925181



065030925181

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date