# APC Smart-UPS 5000VA alimentation d'énergie non interruptible 5 kVA 4000 W



**Marque :** APC

**Code produit:** SUA5000RMT5U

**Nom du produit :** Smart-UPS 5000VA

APC Smart-UPS 5000VA. capacité de la puissance de sortie: 5 kVA, Puissance de sortie: 4000 W, Fréquence d'entrée: 50/60 Hz. Types de sortie AC: NEMA L6-20R, NEMA L6-30R. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 9,4 min, Temps de secours type à demi de charge: 26,7 min. Couleur du produit: Noir, Longueur de câble: 2,44 m. Certification: CSA,FCC Part 15 Class A,UL 1778, RoHS 7b



| Caractéristiques | |
|---|---|
| capacité de la puissance de sortie * | 5 kVA |
| Puissance de sortie * | 4000 W |
| Fréquence d'entrée * | 50/60 Hz |
| Bouton de coupure d'urgence d'alimentation (EPO) | ✔ |
| Niveau sonore | 53 dB |
| Alarmes sonores | ✔ |

| Connectivité | |
|---|---|
| Types de sortie AC | NEMA L6-20R, NEMA L6-30R |

| Batterie | |
|---|---|
| Technologie batterie | Sealed Lead Acid (VRLA) |
| Temps de secours type au chargement complet | 9,4 min |
| Temps de secours type à demi de charge | 26,7 min |
| Temps de rechargement de la batterie | 3 h |
| Batterie échangeable à chaud | ✔ |

| Design | |
|---|---|
| Longueur de câble | 2,44 m |

| Design | |
|---|---|
| Couleur du produit * | Noir |
| Voyants | ✔ |

| Conditions environnementales | |
|---|---|
| Température d'opération | 0 - 40 °C |
| Température hors fonctionnement | -15 - 45 °C |
| Altitude de fonctionnement | 0 - 3000 m |
| Altitude de non fonctionnement | 0 - 15000 m |

| Certificat | |
|---|---|
| Certification | CSA,FCC Part 15 Class A,UL 1778, RoHS 7b |

| Poids et dimensions | |
|---|---|
| Poids | 97,7 kg |

| Données logistiques | |
|---|---|
| Code du système harmonisé | 85078000 |

| Autres caractéristiques | |
|---|---|
| Interface | DB-9 RS-232, SmartSlot |
| Connexions de sortie | 2x NEMA L6-20R 2x NEMA L6-30R |
| Type de connexion d'entrée | NEMA L6-30P |
| Dimensions (LxPxH) | 483 x 660 x 222 mm |
| Tension nominale de sortie | 208 V |
| Tension nominale à l'entrée | 208 V |

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date



0731304255338



731304255338

**Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date