APC SURT20KRMXLT-TF5 alimentation d'énergie non interruptible 20 kVA 18 sortie(s) CA



Marque : APC

Code produit: SURT20KRMXLT-TF5

Nom du produit : SURT20KRMXLT-TF5

APC SURT20KRMXLT-TF5. capacité de la puissance de sortie: 20 kVA, Tension de voltage à l'entrée (min): 160 V, Tension de voltage à l'entrée (max): 280 V. Types de sortie AC: NEMA 5–20R, NEMA L6-20R, NEMA L6-30R, Nombre de prises en sortie: 18 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 2,50 h. Format: Rack/Tour, Couleur du produit: Noir, Capacité du rack: 14U. Certification: UL 1778



Caractéristiques	
capacité de la puissance de sortie *	20 kVA
Tension de voltage à l'entrée (min) *	160 V
Tension de voltage à l'entrée (max) *	280 V
Fréquence d'entrée *	50/60 Hz
tension de voltage à la sortie (min)	120 V
Tension de voltage à la sortie (max)	208 V
Intensité (max.)	105 A
Efficacité	94%
Facteur de crête	3:1
Bouton de coupure d'urgence d'alimentation (EPO)	✔
Tension de sortie THD	5%
Courant d'entrée THD	5%
Filtre de bruit EMI/RFI	✔
Filtrage du bruit EMI/RFI	59 dB
Dispositifs de protection électrique	Surcharge
Alarmes sonores	✔

Connectivité	
Types de sortie AC	NEMA 5–20R, NEMA L6-20R, NEMA L6-30R
Nombre de prises en sortie	18 sortie(s) CA
Nombre de ports série	3
Port RS-232	1
Nombre de port ethernet LAN (RJ-45)	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Nombre de cellules de batterie	4
Temps de rechargement de la batterie	2,50 h
Démarrage à froid	✔

Design	
Format *	Rack/Tour
Capacité du rack	14U
Couleur du produit *	Noir
Type d'écran	LCD
Voyants	✔

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-15 - 45 °C
Humidité relative de fonctionnement (H-H)	0 - 95%
Taux d'humidité relative (stockage)	0 - 95%
Altitude de fonctionnement	0 - 3000 m
Altitude de non fonctionnement	0 - 15000 m

Certificat	
Certification	UL 1778

Poids et dimensions	
Largeur	432 mm
Profondeur	773 mm
Hauteur	622 mm
Poids	290,9 kg

Informations sur l'emballage	
Poids du paquet	364,3 kg

Autres caractéristiques	
Nombre de phases	2
Interface	DB-9 RS-232, RJ-45, Smart-Slot
Dimensions (LxPxH)	432 x 773 x 622 mm
Tension nominale de sortie	120-208 V
Description du filtrage	0.3% IEEE
Tension nominale à l'entrée	208 V
Caractéristiques réseau	10/100 Base-T

Autres caractéristiques	
Température d'opération	32 - 104 °F
Protection contre les surcharges	✔
Protection contre la surintensité	✔
Dimensions du colis (LxPxH)	610 x 1003 x 1244 mm

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date