Buffalo TeraStation TS3430DN1602 serveur de stockage NAS Bureau Alpine AL524 2 Go DDR4 16 To HDD Noir



Marque : Buffalo

Famille de produit: TeraStation

Code produit: TS3430DN1602

Nom du produit :
TS3430DN1602

Buffalo TeraStation TS3430DN1602. Type: NAS. Type de châssis: Bureau. Classe de dispositif: Domicile et télétravail. Famille de processeur: Alpine, Modèle de processeur: AL524, Fréquence du processeur: 2 GHz. Mémoire interne: 2 Go, Type de mémoire interne: DDR4. Capacité totale du stockage installé: 16 To, Type de lecteur de stockage installé: HDD



Support de stockage	
Capacité du lecteur de stockage *	8 To
D'interface pour unité de stockage *	Série ATA III
Interfaces de lecteur de stockage prises en charge	Série ATA III
Support RAID *	✔
Niveaux RAID	0, 6, 1, JBOD, 5, 10
Baies de boîtiers échangeables à chaud	✔
Systèmes de fichiers pris en charge	BTRFS
Lecteurs de stockage installés *	✔
Capacité totale du stockage installé *	16 To
Nombre de lecteurs de stockage installés *	2
Nombre d'unités de stockage pris en charge *	4
Type de lecteur de stockage installé *	HDD
Types de lecteurs de stockage pris en charge *	HDD & SSD

Processeur	
Fabricant de processeur *	Annapurna Labs
Famille de processeur *	Alpine
Modèle de processeur *	AL524
Fréquence du processeur *	2 GHz
Nombre de coeurs de processeurs	4

Mémoire	
Mémoire interne *	2 Go
Type de mémoire interne	DDR4

Réseau	
Ethernet/LAN *	✔
LAN Ethernet : taux de transfert des données	1000,2500 Mbit/s

Connectivité	
Port USB *	✔
Quantité de ports de type A USB 3.2 Gen 2 (3.1 Gen 2)	2
Nombre de port ethernet LAN (RJ-45) *	2

Design	
Type de châssis *	Bureau
Couleur du produit	Noir

représentation / réalisation	
Type *	NAS
Classe de dispositif *	Domicile et télétravail
Fonction de sauvegarde *	✔
Gestion basée sur le web	✔
Bouton marche/arrêt intégré	✔
Authentification par mot de passe	✔

Puissance	
Tension d'entrée AC	100 - 240 V
Fréquence d'entrée AC	50/60 Hz

Poids et dimensions	
Largeur *	231 mm
Profondeur *	170 mm
Hauteur *	216 mm
Poids	6,2 kg
Largeur du colis	358 mm
Profondeur du colis	363 mm
Hauteur du colis	310 mm

Poids et dimensions	
Poids du paquet	7,7 kg
Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	10 - 85 °C

0747464136264

747464136264

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date