ATEN VM6809H commutateur vidéo HDMI



Marque : ATEN

Code produit: VM6809H

Nom du produit : VM6809H

- Connexions entrée/sortie HDMI 8 x 9
- Seamless Switch™ –comporte une commutation proche de zéro seconde pour des flux vidéo en continu, la commutation en temps réel et des transmissions de signaux stables HDMI (3D, Deep Color, 4K) ; compatible HDCP 2.2
- Multiples méthodes de contrôle – gestion du système via les boutons-poussoirs du panneau avant et les connexions RS-232, et Ethernet (interface utilisateur graphique Web / Telnet)



Commutateur matriciel HDMI 4K 8 x 9 avec ajusteur
ATEN VM6809H. Port vidéo: HDMI. Matériel: Métal, Couleur du produit: Noir, Distance de fonctionnement maximum: 15 m. Tension d'entrée de l'adaptateur secteur: 100 - 240 V, Fréquence de l'adaptateur secteur: 50/60 Hz, Courant d'entrée de l'adaptateur CA: 1 A. Largeur: 450,3 mm, Profondeur: 432,4 mm, Hauteur: 44 mm. Quantité: 1 pièce(s), Câbles inclus: Secteur

Connectivité	
Port vidéo *	HDMI
Quantité de ports HDMI	17
Version HDMI	2.0
Entrée HDMI	8
Nombre de sorties HDMI	9
ports d'entrée RJ-45	1
3,5 mm de sortie	✔
Port RS-232	1

Caractéristiques	
Matériel	Métal
Couleur du produit	Noir
HDCP	✔
Distance de fonctionnement maximum	15 m
Résolutions graphiques prises en charge	3840 x 2160, 4096 x 2160
Modes vidéo pris en charge	480p, 720p, 1080p
Bande passante	10,2 Gbit/s
Voyants	✔
Bande passante	340 MHz
Résolution maximale	4096 x 2160 pixels
Haut-parleurs intégrés	✘
Compatibilité 3D	✔
Type HD	4K Ultra HD
Capacité du rack	1U
Impédance d'entrée de sync.	100 Ohm

Caractéristiques	
Impédance de sortie	100 Ohm
Version HDCP	2.2

Puissance	
Tension d'entrée de l'adaptateur secteur	100 - 240 V
Fréquence de l'adaptateur secteur	50/60 Hz
Courant d'entrée de l'adaptateur CA	1 A

Poids et dimensions	
Largeur	450,3 mm
Profondeur	432,4 mm
Hauteur	44 mm
Poids	7,05 kg

Contenu de l'emballage	
Quantité	1 pièce(s)
Kit de montage	✔
Manuel d'utilisation	✔
Câbles inclus	Secteur

Conditions environnementales	
Température d'opération	0 - 50 °C
Température hors fonctionnement	-20 - 60 °C
Humidité relative de fonctionnement (H-H)	0 - 80%

Technical details	
Certificats de conformité	RoHS

0672792008283

672792008283

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date